

SINØGRACE The Chemical Company

Water based Adhesive

SA-233L Water based pressure adhesive for PP/PE films

DESCRIPTION	SA-233L is an adhesive specially designed for reverse gravure coaters, for the production of general purpose filmic labels (PP, PE, etc.) or other pressure sensitive materials.	
ТҮРЕ	Acrylic ester aqueous dispersion	
KEY FEATURES	 Non-yellowing Repositionability Excellent balance of tack and shear Ideal for use in general clear and/or coloured polyolefinic film labels Completely replace BASF film adhesive 	
	Appearance	Milky white liquid
TYPICAL PROPERTIES	pH	6.0-8.0
	Solid content	54±1%
	Type of emulsion	Anionic
	Viscosity (25°C)	200-300mPa·s (17S-21S)
	Density (20°C)	1.02 g/cm3
	Surface of the film	Tacky, clear
APPLICATION	 Suitable for PP, PE, and other self-adhesive film materials Adhesion of advertising materials etc. 	
STORAGE	 Available in 200 kg/ barrel or 1000 kg/ barrel (IBC) Store products in tightly closed original containers at 5-35°C 	
AND	 Shole products in tightly closed original containers at 3-33 C Shelf life: 6-9 months from delivery date 	
HANDLING	 According to non-dangerous goods transport 	