



Water based Adhesive

SA-228 Water based dry lamination adhesive

DESCRIPTION	Water based laminating adhesive for paper and BOPP. It adapts to dry lamination quick drying (tunnel drying). Eco-friendly, non-toxic and excellent comprehensive performance. It can replace solvent based laminating adhesive.	
TYPE	Self-crosslinking acrylic polymer dispersion	
KEY FEATURES	 Non-toxic and eco-friendly Self-crosslinking acrylic adhesive Adapt to high machine speed 60m/min Low dosage surface sizing and low cost Good brightness, high peel strength, no bubbles, smooth, good toughness 	
TYPICAL PROPERTIES	Appearance	Milky white liquid
	pH	5.5-7.0
	Solid content	50±1%
	Type of emulsion	Anionic
	Viscosity (25°C)	100-240mPa s
	Initial adhesive	>14# ball
	Holding power	>24h
	180 °Peel strength	>8N/25mm
APPLICATION	 Lamination of plain films (BOPP, PET, PVC, METPET) to printed paper/duplex board 	
STORAGE AND HANDLING	 Available in 200 kg/ barrel or 1000 kg/ barrel (IBC) Store products in tightly closed original containers at 5-35°C Shelf life: 6-9 months from delivery date According to non-dangerous goods transport 	

Anhui Sinograce Chemical Co., Ltd. Add.: Hefei city, Anhui province, China

According to non-dangerous goods transport

Tel: +86-0551-63459511 Mob: +86 15755193346

Email: sales@sinogracechem.com Web: www.sinogracechem.com