



Ceramic Coatings

C-105 Single layer black ceramic non-stick coating

| DESC | TOTO | TIO | M |
|------|------|----------------------------------|------|
| DESC | | $\mathbf{I}\mathbf{I}\mathbf{U}$ | ALV. |

C-105 is single layer ceramic coating, smooth hand feeling, excellent heat resistance, excellent non-stick performance and abrasion resistant It can be used on non-stick cookware and household appliance.

| TYPE | Ceramic nano material | | |
|--------------------|---|--------------|--|
| KEY | PFOA free | | |
| PA PLY | • Excellent heat resistant (>400°C) | | |
| FEATURES | Excellent non-stick performance and easy to clean | | |
| realuses | Superior chemical resistance and abrasive resistance | | |
| | Appearance | Black | |
| | Solid content (%) | 52±1 | |
| TYPICAL PROPERTIES | Viscosity (cp) | 600~1000 | |
| | Density (g/ml) | 1.20 | |
| | Color of the film surface | Black | |
| | Curing temperature (℃) | 280-300 | |
| | Gloss (60 ° glossimeter) | >35 | |
| | Film thickness (μm) | 30-45 | |
| | Non-stick performance Fry eggs at 170±10°C | >10 cycles | |
| | Corrosion resistance Boling 10% salt water for 24 hours | No blister | |
| | Abrasion resistance 3KG/21cm² | >8000 cycles | |
| | Hardness (ZHONGHUA pencil) | >6H | |

APPLICATION

Aluminum and stainless steel fry pan, wok, soup pot, rice cooker, electric pressure cooker, electric saucepan, electric baking tray, cake mould etc.

STORAGE

• Available in 20 kg/ barrel or 30 kg/ barrel

AND

Store products in tightly closed original containers at 5-40°C
Shelf life: 9 months from delivery date

- 511011 1110. 5 1

According to non-dangerous goods transport

HANDLING

Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589