



## **Architectural Coatings**

## **SA-218 Styrene Acrylic Emulsion for Exterior wall Coatings**

DESCRIPTION	SA-218 is a multi-color paint for the external walls of the emulsion, environmentally friendly non-toxic, the emulsion have a good protective for the color particle.	
ТҮРЕ	Styrene acrylic emulsion	
KEY	<ul> <li>Good construction stability</li> <li>For water-based colorful paint</li> <li>Low VOC, no APEO, health and environmental protection</li> <li>Color point toughness is high, stable and good, anti-bleeding</li> </ul>	
FEATURES	<ul> <li>Excellent water resistance, weather resistance, high fullness</li> <li>Good stability (including its mechanical stability, heat treatment stability)</li> </ul>	
	Appearance	Milky white liquid
	pH	8-9
	Solid content	53±1%
<b>TYPICAL</b>	<b>Glass Transition Temperature</b>	23℃
	Viscosity (25℃)	200-500cP
PROPERTIES	Ca2+ stability 5%CaCl2: emulsion =1:3, 48h, No Flocculation, No Stratification.	Pass
	MFFT	5℃
APPLICATION	High-quality multi-color particle emulsion	
STORAGE	• Available in 200 kg/ barrel or 25 kg/ barrel	
AND	<ul> <li>Store products in tightly closed original containers at 5-40°C</li> <li>Shelf life: 9 months from delivery date</li> </ul>	
HANDLING	<ul> <li>According to non-dangerous goods transport</li> </ul>	

Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589